




# Bekaert Non-Climb and Sheep and Goat Fence

## What can we offer you?

We at Bekaert want to help you select the best “S” knot fence to meet your unique fencing needs. The "S" knot design uses a separate piece of wire that attaches the line wire to the solid stay wire assuring maximum strength and prevents the fence from buckling or sagging. This design is smooth to the touch so you won't have to worry about injuries to your animals. The knot's strength holds up to even the strongest animal or weather impact while maintaining flexibility.



Bekaert “S” knot fences can be used for various applications and many use it as a decorative fence due to its aesthetic appeal and our “S” knot fences ensure a solid construction on most terrains. They are offered in a variety of strength, coatings and styles.



**MADE IN THE USA**

## Animal Applications



## Bekaert Non-Climb and Sheep and Goat Fence Knot Products

### ZA High Strength Horse Fence



- Superior coating resistance
- 95% Zinc; 5% Aluminum
- High Strength wire is 40% stronger than low carbon wire
- Meets/Exceeds ASTM A 856 for Zinc Aluminum standards

### ZA Sheep and Goat Fence



- Superior coating resistance
- 95% Zinc; 5% Aluminum
- High Strength wire is 40% stronger than low carbon wire
- Meets/Exceeds ASTM A 856

### Horseman®



- ZA+ Paint and Class 3 coating offered
- ZA+ Paint: 95% Zinc; 5% Aluminum; UV stabilized black aesthetically pleasing paint
- Class 3 galvanized coating lasts 3 times longer than Class 1
- Meets/Exceeds ASTM A 856

# Bekaert Non-Climb and Sheep and Goat Product Details

## ZA High Strength Horse Fence

Our ZA High Strength Horse fences have closely spaced 2" x 4" openings to prevent horses from stepping through the fence and becoming tangled. Bekaert ZA High Strength Horse Fence is made from high strength steel. The use of high strength wire means that our fence is both stronger and easier to install. Because of its stronger line wires and lighter weight, it requires fewer posts during installation. ZA High Strength Horse fencing have a technically designed coating exclusively made by Bekaert. Bekaert ZA (95% Zinc, 5% Aluminum) coating maximizes fence life and value. Adding 5% Aluminum results in a coating that lasts three times longer than Class 1 at a better value.

| Part Number | Fence Design | Height | Vertical Spacing | Roll Length | Line Wire Diameter | Stay Wire Diameter | Roll Weight | Coating |
|-------------|--------------|--------|------------------|-------------|--------------------|--------------------|-------------|---------|
| 164395      | 1348-2       | 48"    | 2"               | 100'        | 12.5g              | 14g                | 101 lbs     | ZA      |
| 164396      | 1348-2       | 48"    | 2"               | 200'        | 12.5g              | 14g                | 198 lbs     | ZA      |
| 164397      | 1660-2       | 60"    | 2"               | 100'        | 12.5g              | 14g                | 125 lbs     | ZA      |
| 164399      | 1660-2       | 60"    | 2"               | 200'        | 12.5g              | 14g                | 246 lbs     | ZA      |
| 165031      | 1972-2       | 72"    | 2"               | 100'        | 12.5g              | 14g                | 138 lbs     | ZA      |



MADE IN THE USA

## Where to find us

Please do not hesitate to get in touch. We would be delighted to talk about how we can be *better together*.

For more information about Bekaert products scan the QR code or visit our website at:

[fencing.bekaert.com](http://fencing.bekaert.com)



## ZA High Strength Sheep and Goat Fence

Our ZA High Strength Sheep and Goat fences have 4" x 4" openings which are made from high strength steel. Strong knots help keep sheep and goats confined. ZA Sheep and Goat fencing have a technically designed coating exclusively made by Bekaert. Bekaert ZA (95% Zinc, 5% Aluminum) coating maximizes fence life and value. Adding 5% Aluminum results in a coating that lasts three times longer than Class 1 at a better value.

| Part Number | Fence Design | Height | Vertical Spacing | Roll Length | Top and Bottom Wire Diameter | Filler Wire Diameter | Roll Weight | Coating |
|-------------|--------------|--------|------------------|-------------|------------------------------|----------------------|-------------|---------|
| 213412      | 1348-4       | 48"    | 4"               | 330'        | 12.5g                        | 14g                  | 218 lbs     | ZA      |

## Horseman®

Our Horseman® fences have closely spaced 2" x 4" openings to prevent horses from stepping through the fence and becoming tangled. Horseman® is offered in Class 3 and Black ZA+ Paint coating; Bekaert ZA+ Paint (95% Zinc, 5% Aluminum+ UV stabilized black paint) coating lasts three times longer than Class 1, which maximizes fence life and value.

| Part Number | Fence Design | Height | Vertical Spacing | Roll Length | Top and Bottom Wire Diameter | Filler Wire Diameter | Roll Weight | Coating    |
|-------------|--------------|--------|------------------|-------------|------------------------------|----------------------|-------------|------------|
| 118157      | 1348-2       | 48"    | 2"               | 100'        | 10g                          | 12.5g                | 122 lbs     | Class 3    |
| 118232      | 1348-2       | 48"    | 2"               | 200'        | 10g                          | 12.5g                | 244 lbs     | Class 3    |
| 118183      | 1660-2       | 60"    | 2"               | 100'        | 10g                          | 12.5g                | 151 lbs     | Class 3    |
| 134801      | 1348-2       | 48"    | 2"               | 100'        | 10g                          | 12.5g                | 122 lbs     | ZA + Paint |
| 134804      | 1348-2       | 48"    | 2"               | 200'        | 10g                          | 12.5g                | 244 lbs     | ZA + Paint |
| 134808      | 1660-2       | 60"    | 2"               | 100'        | 12.5g                        | 12.5g                | 151 lbs     | ZA + Paint |

Modifications reserved.

All details describe our products in general form only. For ordering and design only use official specifications and documents. Unless otherwise indicated, all trademarks mentioned in this brochure are registered trademarks of NV Bekaert SA or its subsidiaries. © Bekaert 2012